


set up libero

1



The Libero stands up on its wheels:

Open the screw and take out the fixing rod.


Unfold the bottom legs. The two-man-rods are free to be removed. Then unfold the top leg and remove the remaining rods.


2



Now tip over the Libero onto the top legs. Do so while holding the top legs.

3







Screw back thenut onto the arbour and let the arbor disappear in the corpus. The wheels can be stored in the folding compartment.

Lift up the Libero on the other side and completely fold out both legs. Install the fixing rod and screw until tight. Unlock the bolts, turn down the goal boxes and secure them with the tension locks. Now take off the knurled nut and wheels.


4





Release the tension lock and open up the 4 folding doors. Set in the rods taking care that the brown bearing ring fits into the U-form cut notch. Clap the 4 folding doors and secure with the tension lock.


5






On demand align the water level of the Libero with the adjustable feet. Take the goal roofs out of the folding compartment and fix them above the goal. Finished!


disassemble libero






Take away both goal roofs and put them into the folding compartment with the balls and your knick knack. Take out the wheels and mount them onto to the arbor by fixing them with the knurled nut.

2



Open all four folding doors and take out the players. Close them again and secure them with the tension lock.

3




Open the tension locks below the goal boxes, fold them into the playfield and secure them with the bolts. Detach the fixing rod between the legs and take it out.

4



Lift up the Libero on the front side where the wheels are (the notch below the goal is for your hand). Slightly fold the legs on this side and release the Libero body to the ground.

5



Lift up the Libero on the other side and bring him to stand on its wheels. Store away all rods in sequence of ① - ⑥ below the playfield. Fold the legs above, then store rod ⑦ - ⑧ and secure them with the velcro tape. Then fold the bottom leg, set in the fixing rod ⑤ and screw it tight for secure transportation.